


SLIMLINE – MONOBLOC 50 TYPE 2-1 (50-60 KPH)



Slimline - Monobloc 50

combined keg washing and filling featuring

- integrated hot water - detergent set
- integrated media connection and control system
- one stainless steel base frame

This concept creates the possibility to tailor a machine to your needs.

features

- combined internal and external cleaning
- integrated detergent set (up to 4 media tanks)
- positive internal keg transport
- completely piped and wired
- limited time for installation/commissioning: connect and run
- integrated control cabinet with 15" HMI color display showing process/alarm graphics
- PLC with touchscreen control
- transport in standard container
- small footprint
- remote service and diagnostic system
- safety perimeter by glass panels
- foam cleaning ready
- 2 to 4 active washing heads
- 1 filling head with auto shut off control



technical data

- capacity 50-60 kph (depending on configuration and keg size)
- 10 till 60 l kegs, dia 235-430 mm, H 300 to 620 mm
- filling accuracy $\pm 1,25\%$ (- $\pm 0,2\%$ with BPCU)
- CO² loss - 0,0-0,1 g/l
- O² pick up - 0,08 ppm (/ 0,05 ppm with BPCU)
- noise level < 80 dbA
- dimensions: L 3375 mm x W 1700 mm x H 2510 mm production (H 2200 transport)
- weight: empty 2300 kg / production 2750 kg
- power 230/400 V - 50/60 Hz - 4-12 kW (depending on configuration)
- shipping form: one 20' container = 1 TEU

options

- automatic detergent dosing system
- flow meter with automatic back pressure control unit (BPCU)
- auxiliary machines (weigher, turner, coder, keg conveying, palletizing)
- integrated weighing scale

